

## NOVELTY



Lampada a sospensione in alluminio estruso disponibile in diametro 22mm/32 mm e rispettive lunghezze 850mm/650mm.  
Lampada a sospensione e plafone alluminio estruso con diametro 55 mm e lunghezza 450 mm. La versione con diametro 55mm prevede la possibilità di installare tre ottiche con fascio 25°, 34°, 48°. Sorgente luminosa composta da modulo LED ad elevate prestazioni CRI>90 2700K. Rosone con driver ON/OFF integrato nella versione diametro 22mm. Driver ON/OFF integrato nel cilindro nella versione 32mm e 55mm. Finitura con vernice poliacrilica in nero gommato o bianco o finitura in foglia oro decorata a mano. Cavo elettrico trasparente ultrasottile. Ideale per ristoranti, zone living, camere da letto o per creare grandi composizioni a cascata.

Aluminum extruded suspension lamp in 22mm/32mm diameter (si potrebbe usare simbolo diametro) and respectively 850mm/650mm length. Aluminum extruded suspension and ceiling lamp in 55mm diameter and length 450mm. The version in diameter 55mm is available with three different beam angles 25°, 34°, 48°. Light sources made of highly performing LED module with CRI>90 2700K. Canopy with ON/OFF driver integrated in the version 22mm diameter. Integrated ON/OFF driver inside the cylinder for the versions 32mm and 55mm. Finish in polyacrylic rubber black paint or polyacrylic white or hand-made decorated in golden leaf. Ultra-thin transparent electrical cable. Ideal for restaurants, living areas, bedrooms, and to create big cascading compositions.

PAGE CATALOGUE 66

CODICE  
CODEFONTI LUMINOSE  
LIGHT SOURCES

Kgn

**L02501.085.0501**


Potenza assorbita apparecchio / Luminaire power consumption 4W

**L02504.085.0501**

Flusso luminoso apparecchio / Luminaire luminous flux 220 lm

**L02521.085.0501**

2700K Ra 90 220-240V

**L02601.065.0501**


Potenza assorbita apparecchio / Luminaire power consumption 7W

**L02604.065.0501**

Flusso luminoso apparecchio / Luminaire luminous flux 440 lm

**L02621.065.0501**

2700K Ra 90 220-240V

**L02701.045.1701**


Potenza assorbita apparecchio / Luminaire power consumption 10W


**L02704.045.1701**


Flusso luminoso apparecchio / Luminaire luminous flux 900 lm

**L02721.045.1701**

2700K Ra 90 FL 34° 220-240V

	CODICE CODE	FONTE LUMINOSE LIGHT SOURCES	Kgn
 <p>No rosone/driver No canopy/no driver</p>	<b>M02501.085.0510</b>	Potenza assorbita apparecchio / Luminaire power consumption 2,8W	
	<b>M02504.085.0510</b>	Flusso luminoso apparecchio / Luminaire luminous flux 220 lm 2700K Ra 90 24V	
	<b>M02521.085.0510</b>		

	<b>M02601.065.0510</b>	Potenza assorbita apparecchio / Luminaire power consumption 5,3W	
	<b>M02604.065.0510</b>	Flusso luminoso apparecchio / Luminaire luminous flux 440 lm 2700K Ra 90 24V	
	<b>M02621.065.0510</b>		

	<b>P02701.045.1701</b>	Potenza assorbita apparecchio / Luminaire power consumption 10W	
	<b>P02704.045.1701</b>	Flusso luminoso apparecchio / Luminaire luminous flux 900 lm 2700K Ra 90 FL 34° 220-240V	
	<b>P02721.045.1701</b>		

Per progetti a richiesta ottiche a 25° e 48° / For project, beam angles 25°, 48° on request

Fotometrie e Classi Energetiche disponibili [www.panzeri.it](http://www.panzeri.it) / Photometric data and Energy Label available at [www.panzeri.it](http://www.panzeri.it)

#### CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

**01** Bianco / White  
**04** Nero gommato / Rubber black  
**21** Foglia oro / Gold leaf